



FOOTNOTES:

- 1) Due to manufacturers tolerances and continual product improvement, this specification can be subject to variance of plus or +/- 3%.
- 2) Without front riggings
- 3) Varies with user weight, terrain, battery type, battery condition and tire pressure. This specification can be subject to a variance of +/- 10%.
- 4) With rear caster suspension
- 5) Base weight does not include seat or battery weights.
- 6) Standard high-back seat weight is 42.5 lbs.
- 7) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, & ISO 71764 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities.
- 8) 200 lbs. weight capacity
- 9) Solid and pneumatic tires are available; solid tires may incur an upcharge if not included in package.
- 10) Battery weight may vary based on manufacturer.
- 11) Max. speed of 4 mph on XL model
- 12) Shown with optional high-back seat



| | Jazzy Select® Traveller | Jazzy Select® GT | Jazzy Select® 12 | Jazzy Select® 6 12 | Jazzy Select® 6 Ultra ¹² | Jazzy Select® 14 12 | Jazzy® 1113 ATS | Jazzy® 600 12 | Jazzy® 614 12 and 614 HD | Jazzy® 1170 XL Plus | Jazzy® 1420 | Jazzy® 1650 | |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| Weight Capacity | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. | 300 lbs. (HD: 450 lbs.) | 500 lbs. | 500 lbs. | 650 lbs. | |
| Turning Radius ¹ | 22.75" | 20" | 20" | 20.5" | 20.5" | 21" | 20.5" | 20" | 20" | 26.75" | 25.75" | 26.25" | |
| Width ¹ | 21.5" | 23.75" | 23.75" | 23.5" | 23.5" | 24.75" | 23" | 23" | 25.125" | 30" | 27.25" | 30.375" | |
| Length ^{1,2} | 27.75" | 35.5" | 35.5" | 36.625" | 36.625" | 38" | 36" | 36.5" | 35.5" | 45.25" | 46" | 47" | |
| Maximum Speed ³ | Up to 3.5 mph | Up to 4 mph | Up to 4 mph | Up to 4 mph | Up to 4 mph | Up to 5 mph | Up to 4 mph | Up to 5 mph | Up to 4.25 mph | Up to 5 mph | Up to 4.5 mph | Up to 5 mph | |
| Ground Clearance ¹ | 1.75" | 1.875" at center frame | 1.875" at center frame | 2" | 2" | 3" | 2.5" | 3" | 2.25" | 4" | 4.5" | 4.25" | |
| Front Wheels | 5" solid casters | 5" solid anti-tips | 5" solid anti-tips | 6" solid casters | 6" solid casters | 6" solid anti-tips | 6" solid anti-tips | 5" solid OMNI-casters | 6" solid casters | 8" solid anti-tips | 8" solid anti-tips | 8" solid anti-tips | |
| Drive Wheels | 8" solid | 10" solid | 10" solid | 10" solid | 10" solid | 14" solid | 10" ⁹ | 14" ⁹ | 14" | 16" | 16" ⁹ | 16" ⁹ | |
| Rear Wheels | 3" solid anti-tips | 6" solid casters | 6" solid casters | 6" solid casters | 6" solid casters | 8" solid casters | 8" solid casters | 6" solid OMNI-casters | 6" solid casters | 9" solid casters | 9" casters ⁹ | 9" casters ⁹ | |
| Drive Train | Two-motor, in-line, rear-wheel drive | Two-motor, in-line, mid-wheel drive | Two-motor, in-line, mid-wheel drive | Two-motor, in-line, mid-wheel drive | Two-motor, in-line, mid-wheel drive | Two-motor, mid-wheel drive | Two-motor, mid-wheel drive | Two-motor, Mid-Wheel 6 [®] | Two-motor, Mid-Wheel 6 [®] | Two-motor, mid-wheel drive | Two-motor, mid-wheel drive | Two-motor, in-line mid-wheel drive | |
| Braking System | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | Regenerative and electro-mechanical | |
| Suspension Type | Limited | Active-Trac [®] | Active-Trac [®] | Active-Trac [®] | Active-Trac [®] | Limited | Active-Trac [®] | Active-Trac [®] (ATX) | Active-Trac [®] (ATX) | Active-Trac [®] | Active-Trac [®] 4 | Active-Trac [®] Limited | |
| High-Back Seating (max. dimensions) | N/A | only 18"W - 20"W x 20"D | 20"W x 20"D | 20"W x 20"D | 20"W x 20"D | 20"W x 20"D | 20"W x 20"D | 600: 22"W x 20"D | 614: 22"W x 22"D 614 HD: 24"W x 24"D | 28"W x 26"D | 24"W x 24"D | 32"W x 28"D | |
| High-Back Seat to Floor Range | N/A | 19.25" - 21.25" | 19.25" - 21.25" | 19.25" - 21.25" | 22.75" - 26.75" | 23" - 24" | 20" - 21.5" | 21" - 24" | 21.25" - 24.25" | 24" - 25.5" | 22.5" - 24" | 22.75" - 24.25" | |
| Specialty Seating (max. dimensions) | N/A | N/A | 20" x 20" | 20" x 20" | N/A | 20"W x 20"D | 20"W x 18"D | 20"W x 20"D | N/A | N/A | N/A | N/A | |
| Specialty Seat to Floor Range | N/A | N/A | 16.5" - 18.5" | 16.5" - 18.5" | N/A | 18.5" - 19.5" | 14.75" - 16.5" | 17" - 20" | N/A | N/A | N/A | N/A | |
| Synergy Seating (max. dimensions) | N/A | N/A | 20" x 20" | 20" x 20" | N/A | 20" x 20" | 20"W x 18"D | 20"W x 20"D | 22"W x 22"D HD: 24"W x 24"D | N/A | 24"W x 24"D | 32"W x 28"D | |
| Synergy Seat to Floor Range | N/A | N/A | 16.5" - 18.5" | 16.5" - 18.5" | N/A | 18.375" - 19.375" | 15.125" - 17.125" | 17" - 19" | 17.75" - 19.75" | N/A | 18.125" - 20.125" | 18.375" - 20.375" | |
| (without TRU-Balance) Power Elevating Seat Option | N/A | N/A | N/A | N/A | Standard | N/A | N/A | N/A | N/A | N/A | Yes | N/A | |
| TRU-Balance[®] Power Positioning | N/A | N/A | N/A | N/A | N/A | N/A | Tilt or Recline ⁸ | Tilt only | N/A | N/A | N/A | N/A | |
| Specialty Controls | N/A | N/A | N/A | N/A | N/A | N/A | Yes | Yes | N/A | Yes | Yes | Yes | |
| Standard Electronics | 40A, PG GC2 | 40A, PG GC2 | 40A, PG GC2 | 40A, PG GC2 | 40A, PG 6-key VR2 | 60A, Dynamic | 50A, PG VSI | 60A, PG VR2 | 50A, Dynamic | 70A, PG VSI | 70A, PG VR2 | 100A, PG Remote Plus | |
| Battery Size (2 required) | 12 volt, U-1 | 12 volt, U-1 | 12 volt, U-1 | 12 volt, U-1 | 12 volt, U-1 | 12 volt, NF-22 | 12 volt, U-1 | 12 volt, NF-22 | 12 volt, NF-22 | 12 volt, Group 24 | 12 volt, Group 24 | 12 volt, Group 24 | |
| Standard Battery Charger | 3A, off-board | 3A, off-board | 3A, off-board | 3A, off-board | 3A, off-board | 5A, off-board | 4A, on-board | 4A, on-board, standard 5A off-board, optional | 5A, off-board | 5A, off-board | 8A, off-board | 8A, off-board | |
| Per Charge Range ^{3,7} | Up to 15 miles | Up to 15 miles | Up to 15 miles | Up to 15 miles | Up to 15 miles | Up to 15 miles | Up to 15 miles | Up to 20 miles | Up to 16 miles (HD: 11) | Up to 15 miles | Up to 20 miles | Up to 15 miles | |
| Battery Weight ¹⁰ | 24.5 lbs. each | 24.5 lbs. each | 24.5 lbs. each | 24.5 lbs. each | 24.5 lbs. each | 38 lbs. each | 24.5 lbs. each | 38 lbs. each | 38 lbs. each | 53.5 lbs. each | 53.5 lbs. each | 53.5 lbs. each | |
| Base Weight ⁵ | 70 lbs. | 99 lbs. | 99 lbs. | 100 lbs. | 114 lbs. | 105 lbs. | 77 lbs. | 127 lbs. | 121.5 lbs. | 149.5 lbs. | 141.5 lbs. | 176 lbs. | |
| Std. Seat Weight ⁶ | 30 lbs. (contour) | 42.5 lbs. (high-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) | 37 lbs. (medium-back) HD: 42.5 lbs. (high-back) | 42.5 lbs. (high-back) | 42.5 lbs. (high-back) | 75 lbs. (high-back) | |
| Std. Seat Size | 18" x 16" | 18" x 18-20" | 18" x 18" | 18" x 18" | 18" x 18" | 18" x 18" | 18" x 18" | 18" x 18" | 18" x 18" / 20" x 20-18" | 26" x 20" | 22" x 20" | 24" x 20" | |
| Warranty | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | Lifetime on frame; 2-year on electronics; 18-months on motor gearbox | Lifetime on frame; 2-year on electronics; 18-months on motor gearbox | 5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors | Lifetime on frame; 2-year on electronics; 18-months on motor gearbox | Lifetime on frame; 2-year on electronics; 18-months on motor gearbox | Lifetime on frame; 2-year on electronics; 18-months on motor gearbox |

(US) 800-800-8586
(Canada) 888-570-1113
www.pridemobility.com

